

FT 25-RA-60-PSU-M4M

Ordering information

Designation for ordering FT 25-RA-60-PSU-M4M

Part number 604-41000

Order text Working range 20...80 mm, red light, analogue 1...10 V, teach-in, PNP, N.O./N.C, metal connector M8x1, 4-pin For this product there is a new variant 604-41008 FT 25-RA-60-PNSUL-M4M This offers additional functions via IO-Link. Further product information can be found at www.sensopart.de



Components supplied Operating manual, Sensor








Optical data	
Setting range [mm]	20 ... 80
Explanation of the setting range	Reference material 5...90% remission
Resolution [mm]	0.120
Explanation of resolution	12-bit
Linearity [mm]	0.40
Explanation of linearity	± 0.4 mm, reference material gray, 18% remission
Repeatability [mm]	≤ 0.40
Explanation of repeatability	Reference material gray, 18% remission, under constant ambient conditions
Hysteresis [mm]	2.5
Light source	LED
Light color	Red
Wavelength [nm]	632
Light spot size [mm]	See diagram
Switching frequency ≤ [Hz]	≤ 1,000
Explanation of switching frequency	ti/tp 1:1

Functions	
Display, LED yellow	Switching output indicator
Display, LED green	Operating voltage indicator
Setting options	Analogue measurement range QA Invertible analogue characteristic curve Switching output Q (switching window) N.O. / N.C. via teach-in button
Default settings	Analogue output QA (1...10 V): 20...80 mm Switching output Q, N.O. detection range: 20...80 mm
Measuring range adjustment	Via teach-in button


Electrical data	
Operating voltage UB [V DC]	13 ... 30
No-load current [mA]	≤ 30
Output current [mA]	≤ 100
Readiness delay [ms]	≤ 300
Reverse polarity protection	Yes
Short circuit protection	Yes
Response time Q [μs]	≤ 500
Response time QA [μs]	≤ 400.0
Analog output QA	1 ... 10 V / max. 3 mA
Analog output QA voltage [V]	1 ... 10
Measured value output	Analog (voltage)
Protection class	2
Max. capacitive load [nF]	10
Output function	N.O./N.C.
Switching output Q	PNP
Number of outputs	1
Warm-up time [Min.]	10
Temperature profile [mm/K]	0.10

Mechanical data	
Height [mm]	34.0
Length [mm]	20.0
Width [mm]	12.0
Weight [g]	~ 10
Front panel material	PMMA
Housing material	ABS
Ambient temperature: operation [°C]	-20 ... 60
Explanation of operation at ambient air temperature	UL: -20...+50 °C
Ambient temperature: storage [°C]	-20 ... 80
Protection class	IP 67, IP 69
Explanation of protection class	with IP 67 / IP 69 plug connected
Vibration and shock resistance	EN 60947-5-2
Connection name	Metal plug M8x1, 4-pin
- Number of pins	4
- Thread	M8x1
Housing type	Cuboidal


Technical drawings

Dimensional drawing	Plug connection  153-00839
Repeatability (typ.)	 155-03761
Scanning properties	 155-01666
Light spot size	 155-01663
Connections	 154-00543

Characteristic curves



Output and analog characteristic curve



Product link

<https://www.sensopart.com/en/products/details/604-41000>