

# V20-OB-A3-R-N-M2-L

## Ordering information

**Designation for ordering** V20-OB-A3-R-N-M2-L

**Part number** 632-91036

**Order text** VISOR® V20 Object, Advanced, 255 jobs each with 255 detectors, red illumination, narrow field of view, motorized focus, LAN interface, target laser

**Components supplied** VISOR® vision sensor, Operating manual, Mounting bracket (MK 45) and Allen key



EtherNet/IP



| Optical data                    |                    |
|---------------------------------|--------------------|
| Image chip type                 | Monochrome         |
| Light source                    | LED                |
| Light color                     | Red                |
| Wavelength [nm]                 | 625                |
| LED risk category [RG]          | 0                  |
| Explanation of risk category    | Acc. to EN 62471   |
| Resolution                      | HDV2               |
| Number of pixels (H x V) [px]   | 1440 x 1080        |
| Imaging chip technology         | CMOS               |
| Sensor size ["]                 | 1/2.9              |
| Pixel size [μm]                 | 3.45               |
| Field of view type              | Narrow             |
| Operating distance [mm]         | 100 ... 10,000     |
| Focal length [mm]               | 20.0               |
| Opening angle [°]               | 12.0               |
| Min. field of view (X x Y) [mm] | 18 x 14            |
| Aperture number                 | 2.8                |
| Depth of field                  | Standard           |
| Focus drive                     | Motorized          |
| Target laser                    | Laser red (655 nm) |
| Laser class                     | 1 (IEC 60825-1)    |


| Functions                |                                                                                                                                                            |
|--------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Network protocol         | TCP/IP, Profinet, EtherNet/IP, sFTP, SMB, FTP, Service Port                                                                                                |
| Hardware                 | VISOR®                                                                                                                                                     |
| Max. number of jobs      | 255                                                                                                                                                        |
| Max. number of detectors | 255                                                                                                                                                        |
| Alignment                | Contour comparison, Pattern matching, Edge detection                                                                                                       |
| Available detectors      | Pattern matching, Contour, Contour check, BLOB, Brightness, Contrast, Grayscale, Caliper                                                                   |
| Result processing        | Numbers                                                                                                                                                    |
| Pre-processing           | Arrangement, Filter                                                                                                                                        |
| Calibration              | Board (measurement), Scaling (measurement)                                                                                                                 |
| Robotic functions        | -                                                                                                                                                          |
| Additional functions     | Archiving, Image transmission, individual overlays, Multiple image acquisition, Multiple detection for contour and pattern matching detector, Job checksum |

| Electrical data                     |                                                               |
|-------------------------------------|---------------------------------------------------------------|
| Operating voltage UB [V DC]         | 18 ... 30                                                     |
| Typical current draw [mA]           | 350                                                           |
| Type of voltage source              | The device must be supplied by a "Class 2" power supply unit. |
| Readiness delay [ms]                | ≤ 16,000                                                      |
| Reverse polarity protection         | Yes                                                           |
| Overvoltage protection              | No                                                            |
| Residual ripple [%]                 | ≤ 5 Vss, level 3                                              |
| Explanation of residual ripple      | EN 61000-4-17                                                 |
| Polarity                            | PNP/NPN                                                       |
| Short circuit protection            | Yes                                                           |
| Input threshold (High)              | > UB-1V                                                       |
| Input threshold (Low)               | < 3V                                                          |
| Input resistance [kΩ]               | > 20                                                          |
| Max. output current [mA]            | 50                                                            |
| Explanation of max. output current  | max. 100 mA on pin 12                                         |
| Inductive loads                     | Typ.: Relay 17 K / 2 H, pneumatic valve 1.4 K / 190 mH        |
| Max. output current (total) [mA]    | 200                                                           |
| Ethernet transmission rate [Mbit/s] | 100                                                           |
| Number of switchable IOs            | 6                                                             |
| Number of outputs                   | 2                                                             |
| Number of inputs                    | 2                                                             |
| Encoder functions                   | Yes                                                           |

| Mechanical data                               |                                                               |
|-----------------------------------------------|---------------------------------------------------------------|
| Height [mm]                                   | 85.0                                                          |
| Length [mm]                                   | 45.0                                                          |
| Width [mm]                                    | 45.0                                                          |
| Weight [g]                                    | ~ 220                                                         |
| Front panel material                          | PMMA                                                          |
| Housing material                              | Aluminum (cast)                                               |
| Connection name                               | Supply                                                        |
| - Number of pins                              | 12                                                            |
| - Coding                                      | A                                                             |
| - Thread                                      | M12x1                                                         |
| - Material                                    | Metal                                                         |
| - Type                                        | Plug                                                          |
| Connection name                               | LAN                                                           |
| - Number of pins                              | 4                                                             |
| - Coding                                      | D                                                             |
| - Thread                                      | M12x1                                                         |
| - Material                                    | Metal                                                         |
| - Type                                        | Socket                                                        |
| Ambient temperature: operation [°C]           | 0 ... 50                                                      |
| Explanation of ambient temperature: operation | < 95 % humidity, non-condensing                               |
| Ambient temperature: storage [°C]             | -20 ... 60                                                    |
| Explanation of ambient temperature: storage   | < 95 % humidity, non-condensing                               |
| Protection class                              | IP 65, IP 67                                                  |
| Explanation of protection class               | For C-mount devices, only in combination with protective tube |
| Vibration and shock resistance                | EN 60068-2-6, EN 60068-2-27                                   |


Technical drawings

Dimensional drawing



153-13554

Field of view



155-00098

Product link

<https://www.sensopart.com/en/products/details/632-91036>