

# V20-CR-A4-R-MD-M3-L

## Ordering information

|                                 |                                                                                                                                                    |
|---------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Designation for ordering</b> | V20-CR-A4-R-MD-M3-L                                                                                                                                |
| <b>Part number</b>              | 637-91051                                                                                                                                          |
| <b>Order text</b>               | VISOR® XE V20 Code Reader Advanced, red illumination, medium field of view, increased depth of field, motorized focus, LAN interface, target laser |
| <b>Components supplied</b>      | VISOR® XE vision sensor, Operating manual, Mounting bracket (MK 45) and Allen key                                                                  |



| Optical data                    |                    |
|---------------------------------|--------------------|
| Image chip type                 | Monochrome         |
| Light source                    | LED                |
| Light color                     | Red                |
| Wavelength [nm]                 | 625                |
| LED risk category [RG]          | 0                  |
| Resolution                      | SPXGA              |
| Number of pixels (H x V) [px]   | 1600 x 1200        |
| Imaging chip technology         | CMOS               |
| Sensor size ["]                 | 1/2.9              |
| Pixel size [μm]                 | 3.00               |
| Field of view type              | Mittel             |
| Operating distance [mm]         | 30 ... 10,000      |
| Focal length [mm]               | 12.0               |
| Opening angle [°]               | 23.0               |
| Min. field of view (X x Y) [mm] | 13.5 x 10.1        |
| Aperture number                 | 5.6                |
| Depth of field                  | Enhanced           |
| Focus drive                     | Motorized          |
| Target laser                    | Laser red (655 nm) |
| Laser class                     | 1 (IEC 60825-1)    |


| Functions                |                                                                                              |
|--------------------------|----------------------------------------------------------------------------------------------|
| Hardware                 | VISOR® XE                                                                                    |
| Max. number of jobs      | 255                                                                                          |
| Max. number of detectors | 255                                                                                          |
| Alignment                | -                                                                                            |
| Available detectors      | Data code, Barcode                                                                           |
| Result processing        | Text                                                                                         |
| Pre-processing           | Arrangement, Filter                                                                          |
| Calibration              | -                                                                                            |
| Robotic functions        | -                                                                                            |
| Additional functions     | Archiving, Image transmission, individual overlays, Multiple image acquisition, Job checksum |

| Electrical data                     |                                                               |
|-------------------------------------|---------------------------------------------------------------|
| Operating voltage UB [V DC]         | 18 ... 30                                                     |
| Typical current draw [mA]           | 350                                                           |
| Type of voltage source              | The device must be supplied by a "Class 2" power supply unit. |
| Readiness delay [ms]                | ≤ 16,000                                                      |
| Reverse polarity protection         | Yes                                                           |
| Overvoltage protection              | No                                                            |
| Residual ripple [%]                 | ≤ 5 Vss, level 3                                              |
| Explanation of residual ripple      | EN 61000-4-17                                                 |
| Polarity                            | PNP/NPN                                                       |
| Short circuit protection            | Yes                                                           |
| Input threshold (High)              | > UB-1V                                                       |
| Input threshold (Low)               | < 3V                                                          |
| Input resistance [kΩ]               | > 20                                                          |
| Max. output current [mA]            | 50                                                            |
| Explanation of max. output current  | max. 100 mA on pin 12                                         |
| Inductive loads                     | Typ.: Relay 17 K / 2 H, pneumatic valve 1.4 K / 190 mH        |
| Max. output current (total) [mA]    | 200                                                           |
| Ethernet transmission rate [Mbit/s] | 100                                                           |
| Number of switchable IOs            | 6                                                             |
| Number of outputs                   | 2                                                             |
| Number of inputs                    | 2                                                             |
| Encoder functions                   | No                                                            |


| Mechanical data                               |                                                               |
|-----------------------------------------------|---------------------------------------------------------------|
| Height [mm]                                   | 85.0                                                          |
| Length [mm]                                   | 45.0                                                          |
| Width [mm]                                    | 45.0                                                          |
| Weight [g]                                    | ~ 220                                                         |
| Front panel material                          | PMMA                                                          |
| Housing material                              | Aluminum (cast)                                               |
| Connection name                               | Supply                                                        |
| - Number of pins                              | 12                                                            |
| - Coding                                      | A                                                             |
| - Thread                                      | M12x1                                                         |
| - Material                                    | Metal                                                         |
| - Type                                        | Plug                                                          |
| Connection name                               | LAN                                                           |
| - Number of pins                              | 4                                                             |
| - Coding                                      | D                                                             |
| - Thread                                      | M12x1                                                         |
| - Material                                    | Metal                                                         |
| - Type                                        | Socket                                                        |
| Ambient temperature: operation [°C]           | 0 ... 50                                                      |
| Explanation of ambient temperature: operation | < 95% humidity, non-condensing                                |
| Ambient temperature: storage [°C]             | -20 ... 60                                                    |
| Explanation of ambient temperature: storage   | < 95% humidity, non-condensing                                |
| Protection class                              | IP 65, IP 67                                                  |
| Explanation of protection class               | For C-mount devices, only in combination with protective tube |
| Vibration and shock resistance                | EN 60068-2-6, EN 60068-2-27                                   |

Technical drawings

Dimensional drawing



Field of view



Product link

<https://www.sensopart.com/en/products/details/637-91051>