


# V50-CR-P3-C-2-P

## Ordering information

|                                 |                                                                                      |
|---------------------------------|--------------------------------------------------------------------------------------|
| <b>Designation for ordering</b> | V50-CR-P3-C-2-P                                                                      |
| <b>Part number</b>              | 635-91106                                                                            |
| <b>Order text</b>               | VISOR® V50 Code Reader, Professional, C-Mount, LAN, EIP, PROFINET, polarizing filter |
| <b>Components supplied</b>      | VISOR® vision sensor, Operating manual, Mounting bracket (MK 45) and Allen key       |



EtherNet/IP™

## Optical data


|                                        |                                                      |
|----------------------------------------|------------------------------------------------------|
| <b>Image chip type</b>                 | Monochrome                                           |
| <b>Resolution</b>                      | QSXGA                                                |
| <b>Number of pixels (H x V) [px]</b>   | 2560 x 1936                                          |
| <b>Imaging chip technology</b>         | CMOS                                                 |
| <b>Sensor size ["]</b>                 | 1/1.8                                                |
| <b>Pixel size [μm]</b>                 | 2.80                                                 |
| <b>Field of view type</b>              | C-Mount (field-of-view data depend on the lens used) |
| <b>Min. field of view (X x Y) [mm]</b> | Abhängig vom gewählten Objektiv                      |
| <b>Focus drive</b>                     | Dependent on the objective lens selected             |

## Functions

|                                 |                                                                                                                      |
|---------------------------------|----------------------------------------------------------------------------------------------------------------------|
| <b>Hardware</b>                 | VISOR®                                                                                                               |
| <b>Max. number of jobs</b>      | 255                                                                                                                  |
| <b>Max. number of detectors</b> | 255                                                                                                                  |
| <b>Alignment</b>                | Contour comparison, Pattern matching, Edge detection                                                                 |
| <b>Available detectors</b>      | Pattern matching, Data code, Barcode, OCR, Brightness, Contrast, Gray level                                          |
| <b>Result processing</b>        | Text                                                                                                                 |
| <b>Pre-processing</b>           | Arrangement, Filter                                                                                                  |
| <b>Calibration</b>              | -                                                                                                                    |
| <b>Robotic functions</b>        | -                                                                                                                    |
| <b>Additional functions</b>     | Archiving, Image transmission, individual overlays, Multiple image acquisition, Job checksum, Conditional executions |
| <b>Network protocol</b>         | TCP/IP, Profinet, EtherNet/IP, sFTP, SMB, FTP, Service Port                                                          |

| Electrical data                     |                                                               |
|-------------------------------------|---------------------------------------------------------------|
| Operating voltage UB [V DC]         | 18 ... 30                                                     |
| Typical current draw [mA]           | 350                                                           |
| Type of voltage source              | The device must be supplied by a "Class 2" power supply unit. |
| Readiness delay [ms]                | ≤ 16,000                                                      |
| Reverse polarity protection         | Yes                                                           |
| Overvoltage protection              | No                                                            |
| Residual ripple [%]                 | ≤ 5 Vss, level 3                                              |
| Explanation of residual ripple      | EN 61000-4-17                                                 |
| Polarity                            | PNP/NPN                                                       |
| Short circuit protection            | Yes                                                           |
| Input threshold (High)              | > UB-1V                                                       |
| Input threshold (Low)               | < 3V                                                          |
| Input resistance [kΩ]               | > 20                                                          |
| Max. output current [mA]            | 50                                                            |
| Explanation of max. output current  | max. 100 mA on pin 12                                         |
| Inductive loads                     | Typ.: Relay 17 K / 2 H, pneumatic valve 1.4 K / 190 mH        |
| Max. output current (total) [mA]    | 200                                                           |
| Ethernet transmission rate [Mbit/s] | 100                                                           |
| Number of switchable IOs            | 6                                                             |
| Number of outputs                   | 2                                                             |
| Number of inputs                    | 2                                                             |
| Encoder functions                   | Yes                                                           |

| Mechanical data                               |                                                               |
|-----------------------------------------------|---------------------------------------------------------------|
| Height [mm]                                   | 85.0                                                          |
| Length [mm]                                   | 45.0                                                          |
| Width [mm]                                    | 45.0                                                          |
| Weight [g]                                    | ~ 220                                                         |
| Front panel material                          | PMMA                                                          |
| Housing material                              | Aluminum (cast)                                               |
| Connection name                               | Supply                                                        |
| - Number of pins                              | 12                                                            |
| - Coding                                      | A                                                             |
| - Thread                                      | M12x1                                                         |
| - Material                                    | Metal                                                         |
| - Type                                        | Plug                                                          |
| Connection name                               | LAN                                                           |
| - Number of pins                              | 4                                                             |
| - Coding                                      | D                                                             |
| - Thread                                      | M12x1                                                         |
| - Material                                    | Metal                                                         |
| - Type                                        | Socket                                                        |
| Ambient temperature: operation [°C]           | 0 ... 50                                                      |
| Explanation of ambient temperature: operation | < 95 % humidity, non-condensing                               |
| Ambient temperature: storage [°C]             | -20 ... 60                                                    |
| Explanation of ambient temperature: storage   | < 95 % humidity, non-condensing                               |
| Protection class                              | IP 65, IP 67                                                  |
| Explanation of protection class               | For C-mount devices, only in combination with protective tube |
| Vibration and shock resistance                | EN 60068-2-6, EN 60068-2-27                                   |



**Product link**

<https://www.sensopart.com/en/products/details/635-91106>