

FR 18-2

Photoelectric retro-reflective sensor





PRODUCT HIGHLIGHTS



- Economical solution for numerous applications
- Range of up to 3.0 m
- Variants with angled light exit
- Polarisation filter for reliable detection of highly reflective surfaces
- Simple adjustment via potentiometer
- 2 through holes as additional mounting possibility


Optical data		Functions	
Operating range	See selection table ¹	Indicator LED, green	Operating voltage indicator
Type of light	See selection table	Indicator LED, yellow	Switching output indicator
Polarising filter	Yes	Sensitivity adjustment	Via potentiometer
		Adjustment possibilities	N.O./N.C. via control input (IN)
		Default settings	Max. scanning distance and N.O.
Electrical data		Mechanical data	
Operating voltage, +U _B	10 ... 30V DC	Dimensions	See dimensional drawings
No-load current, I ₀	≤ 30 mA	Enclosure rating	IP 67 ²
Output current, I _e	≤ 100 mA	Material, housing	Brass, nickel-plated
Protective circuits	Reverse-polarity protection, U _B / short-circuit protection	Material, front screen	PMMA
Switching output, Q	PNP/NPN (see selection table)	Type of connection	See selection table
Output function	N.O./N.C.	Ambient temperature: operation	-25 ... +55 °C
Switching frequency, f (ti/tp 1:1)	≤ 1000 Hz	Weight (plug device)	34 g ³ / 36 g ⁴
Response time	≤ 1 ms	Weight (cable device)	74 g ³ / 76 g ⁴
		Max. tightening torque	3 Nm

¹ Reference material: R5 reflector ² With connected IP 67 plug ³ Straight light exit variant ⁴ Angled light exit variant

Operating range	Type of light	Light exit	Switching output	Type of connection	Part number	Article number
3.0 m	Red light	Straight	PNP	Metal plug, M12, 4-pin	FR 18-2 RM-PS-L4	741-11014
3.0 m	Red light	Straight	NPN	Metal plug, M12, 4-pin	FR 18-2 RM-NS-L4	741-11015
3.0 m	Red light	Straight	PNP	Cable, 2 m, 4-wire	FR 18-2 RM-PS-K4	741-11016
3.0 m	Red light	Straight	NPN	Cable, 2 m, 4-wire	FR 18-2 RM-NS-K4	741-11017
2.4 m	Red light	90° angle	PNP	Metal plug, M12, 4-pin	FR 18-2 RWM-PS-L4	741-11018
2.4 m	Red light	90° angle	NPN	Metal plug, M12, 4-pin	FR 18-2 RWM-NS-L4	741-11019
2.4 m	Red light	90° angle	PNP	Cable, 2 m, 4-wire	FR 18-2 RWM-PS-K4	741-11020
2.4 m	Red light	90° angle	NPN	Cable, 2 m, 4-wire	FR 18-2 RWM-NS-K4	741-11021

Plug connection (straight)	Cable connection (straight)
 153-00985	 153-00984

Plug connection (angled)	Cable connection (angled)
 153-00987	 153-00986

Connection, 4-pin
 154-00508

Scope of delivery	Accessories
Sensor Reflector: 53.4 x 53.4 mm ² 2 x securing nuts	Reflectors Connection cables Brackets
	www.sensopart.com/en/accessories